

# DucoClose 35Z

## Architectural Grilles






- + Applicable as louvre grille (with or without flange)
- + Applicable as glazed-in louvres
- + Superb design both in- and outside
- + Manual or motorised control

Tel 0032-58/33 00 66 - Fax 0032-58/33 00 67 - [info@duco.eu](mailto:info@duco.eu) - [www.duco.eu](http://www.duco.eu)

**DUCO**<sup>®</sup>  
VENTILATION & SUN CONTROL

# DucoClose 35Z

## Architectural Grilles



DucoClose N 35Z and DucoClose G 35Z are operatable 'build-in' louvres which can be integrated easily in all kinds of façades. They provide intensive ventilation.

DucoClose F 35Z is an operatable 'glazed-in' louvre which is ideal for the application of Night Cooling. The smooth designed "Z" blades provide adjustable ventilation by means of manual or motorised control. Standard colour is SAA (15-20µm). All RAL colours (60-80µm) are available on request. DucoClose is optionally available with insect or bird screen.

### Technical Specifications

Type of blade	35
Blade height	40 mm
Pitch	50 mm
Thickness of the frame	42 mm (N 35Z & G 35Z)
Minimal height	123,50 mm (manual control) 473,50 mm (motorised control)
Free area (open position)	51 %
Nett airflow (open position)	39 %

Material : Aluminium Al Mg Si 0,5

Surface treatment :

- Standard colours : SAA (15-20 µm) (15-20 µm) (VB6/A20/VOM1)
- Enamelled polyester powder coating (60-80 µm)

All RAL colours are available

Manual or motorised control

**FAX** ————— **0032-58/33 00 67**

Yes, we would like to receive further information on the DucoClose range.

Yes, we would like to be contacted by your Sales Advisor :

Company : .....

Adress : .....

Phone : .....

Person to contact: .....

Tel 0032-58/33 00 66 - Fax 0032-58/33 00 67 - info@duco.eu - www.duco.eu

**DUCO**<sup>®</sup>  
VENTILATION & SUN CONTROL